

(19)

Japanese Patent Office

(11)

JP 11077650 A

(45)

19990323

---

(21) Application number: **09243257** (51) Int Cl.: **B28B01110**, B28B00152, B28B00302, B28B00502, B28C00700, C04B02802, C04B02802, C04B01410, C04B01602, C04B11120  
(22) Date of filing: **19970909**

---

(54) **MANUFACTURE OF FIBER-REINFORCED CEMENT PLATE**

---

(72) Inventor(s): **KOMATSU KAZUYUKI**  
**HASHI KAZUO**  
**UEMATSU ATSUSHI**  
**KUWAYAMA HIROKI**  
(73) Assignee(s): **KUBOTA CORP**

**Abstract**

(57) **PROBLEM TO BE SOLVED:** To easily manufacture a deeply engraved protrusion and recess pattern on a surface of a fiber-reinforced cement plate to be manufactured by a machine without limiting material.

**SOLUTION:** A one-layer flow-on molding method for lumbering by supplying cement slurry 6 in a laminar state onto a felt belt 5 having a suction dehydrator 4 and suction dehydrating it comprises the steps of supplying the slurry 6 obtained by uniformly dispersing clay particles in fiber-reinforced cement mixture made by normal method mixing onto the belt 5 or a cement layer formed on the belt 5, stratifying it, then cutting it in a size adapted to press molding to be described later, pressing the cut unhardened fiber-reinforced cement plate to form a protrusion and recess pattern, and curing to harden it according to a conventional method.